



- 1 WARM WATER INLET 2x 100 NB FLANGE
TABLE "E" AS 2129
- 2 COLD WATER OUTLET 1x or 2x 150NB - CUT OUT
TABLE "E" AS 2129
- 3 FRESH WATER INLET - 15 NB BSP (M)
- 4 DRAIN 50 NB - TABLE "E" AS 2129 - CUT OUT
- 5 FAN WITH DRIVING MOTOR
AND PROTECTION GRID
- 6 OVERFLOW - 50 NB BSP (F)
- 7 AIR INLET
- 8 AIR OUTLET
- 9 INSPECTION HATCH 500 x 600
- 10 QUICK FILL - 15 NB BSP (M)
- 11 LADDER - VERTICAL - ALUMINIUM
(SPECIAL ACCESSORY)
- 12 SPECIAL LADDER WITH BACKKAGE - H.D.G.S
(SPECIAL ACCESSORY)

Type	DIMENSIONS in mm			
	A	B	C	D
450/09	3983	3583	2951	2713
450/06	3683	3283	2651	2413

PIPING CONNECTIONS

WATER RATE IN	40 - 135 m3/h
WARM WATER INLET	2 x 100 NB
COLD WATER OUTLET	
FOR WATER RATE 40 - 70 m3/h - (I)	1 x 150 NB
FOR WATER RATE 71 - 135 m3/h - (I + II)	2 x 150 NB
OPERATING (+ MAX.) WATER LEVEL	350 +50 MM

WEIGHTS

EMPTY WEIGHT	900 kg
OPERATION WEIGHT	3.000 kg
MAXIMUM WEIGHT	4 000 kg